


# DRIVE-THROUGH DIGITAL MENU BOARDS

3500 - 4000 NIT Ultra High Bright Outdoor  
Digital Menu Board Screen Enclosure.


**SCREEN SIZES: 49" 55" & 75"**

- ✓ UV Resistant Glass
- ✓ 3M UV Sun Control Film
- ✓ IP65 & IP67 Waterproof Design
- ✓ 304 Stainless Steel Finish
- ✓ Black or Custom RAL Finish



## 49", 55" & 75" Models

Built for a range of Drive-Through environments, our versatile enclosures come in 49", 55" & 75" models and the stand plinth can mount a single, double or triple screen setup.



## Standard Finish 304 Stainless Steel

Built with a premium stainless-steel finish, our outdoor screen enclosures come with a 5 YR - Anti-Rust and Corrosion warranty, giving you peace of mind, they will last the test of time.






## LCD Air Curtain Cross Blower Fan

Fans & Tangential Cross Blowers provide an LCD Air-Curtain keeping the hi-bright Display nice and cool for the sunniest days.




## UV Protected with 3M™ Sun Control Film

Tempered Glass is protected with 3M™ Sun Control Film this rejects up to 97% of sun's infrared light and blocks up to 99.9% of harmful ultraviolet (UV) rays. Preventing Screen Blackening & Failure.

## Key Features

-  Standard finish in 304 Stainless Steel
-  3M Sun Control Film
-  Air-cooled & Temperature Controlled
-  24/7 Commercial Use
-  Internal Locker with AV Inputs

## Additional Add-Ons

-  Choice of Commercial Screens - 49" to 75"
-  Windows or Android Media Player
-  Custom RAL Painted Finish and Branding



### Custom RAL Power Coat & Finish

Our Drive-Through Enclosures are proudly Made in Britain, meaning we are able to keep lead times short and offer a bespoke service. We are able to custom fabricate based on requirements and powder coat our enclosures to your brand ral or finish.

### RCD Protected for Electrical & Equipment Safety

All of our outdoor screen enclosures are fitted with a 30mA RCD that protects users and equipment if an electrical fault was ever to occur. If an electrical fault was detected the switch will disconnect power within 40 NanoSeconds.



### IP65 ENCLOSURES Single, Double & Triple Plinth Options

Benefiting from a modular design, the drive-thru enclosures can be fixed to a single, double or triple stand to suit any configuration of screens and drive through locations.

### 55" IP67 WATERPROOF Drive-thru Displays with IK10 Glass 4000 Nits

Kudos Digital offer a range of Plinths for mounting a single, double or triple display, also as part of the Drive -thru range is our a IP Phone and Headset System along with a Stainless Steel Intercom Pillar.





	Size	49"	55"
Panel Information	Panel Type	a-Si TFT-LCD	a-Si TFT-LCD
	Area Area (mm)	1073.8 x 604 mm	1209.6 x 680.4 mm
	Aspect Ratio	16:9	16:9
	Resolution	1920 x 1080px	1920 x 1080px
	Brightness	3500 Nits	3500 Nits
	Contrast Ratio	1400:1	1400:1
	Viewing Angle	178/178	178/178
	Frequency	60Hz	60Hz
	Life Time (LED Backlight)	50,000 Hours	50,000 Hours
Environment	Operating System	0°C ~ 50°C	
	Storage System	-20°C ~ 60°C	
	Power Supply	96V - 220V	
	Rated Frequency	50/60Hz	

