

High Bright Double Sided Displays

Ideal for Shop Fronts & Windows Displays

- ✔ Commercial grade 700NIT (Side 1)
- ✔ 3000NIT window facing (High Bright Side 2)
- ✔ Build-in Android Player
- ✔ USB Plug & Play Media Player
- ✔ Slim Design with Fan Cooling System



MADE IN BRITAIN

3 Years Warranty



32"- 86" Models

Incredibly sleek, stylish and slim yet extremely visible with a choice of sizes; 32" - 86", all with a ultra high bright 3000Nit display. Designed to stand out in busy retail and commercial environments.



Plug & Play (USB) or Cloud CMS Connected

Content can be updated easily via USB with the built-in Media Player or upgrade to a Cloud Connected Media player to schedule content and schedules remotely.



Single & Double Sided Models Available

Attract customers with an ultra high bright 3000NIT external facing display & 700NIT internal facing display. Ideal for south facing locations for your signage to always be visible.



Built in Internal Fan Cooling System

Designed to run High Bright content 24/7, the screens feature built in cooling fans to prevent blackening and screen burn out.

Key Features

- Single & Double Sided Models
- Android Media Player
- Built in Internal Cooling Fans
- Plug & Play Media Player
- 24/7 Commercial Use
- 3500NIT Display

Available Add-ons

- Cloud CMS Software

	Size	49"	55"
Panel Details	Aspect Ratio	16:9, Wide	16:9
	Resolution	1080 x 1920px	1080 x 1920
	Viewing Angle	89/89/89/89	89/89/89/89
	Brightness	3000Nit (Window Facing), 700nits (Internal Facing)	3000Nit (Window Facing), 700nits (Internal Facing)
	Active Area	1073.78 x 604mm	680.4 x 1209.6mm
	Brightness	60Hz	60Hz
	Service Lifetime	50,000 Hours	50,000 Hours
Motherboard	Version	Android 7.1	
	CPU	RK3288, Quad Core	
	ROM	TSD Flash 8G	
	SD Card Slot	Support MAX 128GB	
	Port	USB 2.0, RJ45 x1, HDMI Out x1, VGA Out x1, Lan Port x1	
	Speaker	5W + 5W	
	Language	English & Multiple Languages	
Environment	Operating Temp	0°C~50°C	
	Storage System	-20°C~60°C	
Power	Power Supply	100 - 240V	
	Rated Requency	50/60Hz	



	Size	32"	43"	49"	55"
Panel Details	Panel Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
	Area (mm)	698.4 x 392.85 mm	941.184 x 529.416 mm	1073.8 x 604 mm	1209.6 x 680.4 mm
	Aspect Ratio	16:9	16:9	16:9	16:9
	Resolution	1920 x 1080px	1920 x 1080px	1920 x 1080px	1920 x 1080px
	Brightness	3500 Nits	3500 Nits	3500 Nits	3500 Nits
	Contrast Ratio	1400:1	1400:1	1400:1	1400:1
	Viewing Angle	178/178	178/178	178/178	178/178
	Frequency	60Hz	60Hz	60Hz	60Hz
	Panel Size	65"		75"	86"
	Panel Type	a-Si TFT-LCD		a-Si TFT-LCD	a-Si TFT-LCD
	Area (mm)	1428.48 x 803.52 mm		1649.66 x 927.936 mm	1895.04 x 1065.96 mm
	Aspect Ratio	16:9		16:9	16:9
	Resolution	3840 x 2160px		3840 x 2160px	3840 x 2160px
	Brightness	3500 Nits		3500 Nits	3500 Nits
	Contrast Ratio	1400:1		1400:1	1400:1
	Viewing Angle	178/178		178/178	178/178
	Frequency	60Hz		60Hz	60Hz
	Life Time (LED Backlight)	50,000 Hours		50,000 Hours	50,000 Hours
	Operating System	System	Android 5.1		
CPU		RK3288			
RAM		2GB			
ROM		8GB			
Network		WIFI/RJ45			
I/P Ports		USB 2.0 x2, Micro USB, OTG x1, RJ45 x1, HDMI Out x1, Standard Micro SD Card x1			
Language		English			
Features	Operation	24/7 Non-stop Operation			
	Surface	Anti-Glare 10%			
	Casing Design	Fan-cooling System			
Environment	Operating System	0°C ~ 50°C			
	Storage System	-20°C ~ 60°C			
Power	Power Supply	96V - 220V			
	Rated Requency	50/60Hz			

